



Housing No.	L	b	f1 H13	F H13	D H7	d2 H12	d3 H12	H	A h12	G	E	B	v	u	S	Weight (kg)
SNK 505	67	46	5	25	52	31.5	39.5	74	40	19	130	165	20	15	12	1.45
SNK 506-605	77	52	5	32	62	36.5	44.5	89	50	22	150	185	20	15	12	2.02
SNK 507-606	82	52	5	34	72	46.5	54.5	93	50	22	150	185	20	15	12	2.23
SNK 508-607	85	60	5	39	80	51.5	59.5	107	60	25	170	205	20	15	12	2.89
SNK 509	85	60	5	30	85	56.5	64.5	109	60	25	170	205	20	15	12	2.93
SNK 510-608	90	60	5	41	90	62	70.5	113	60	25	170	205	20	15	12	3.24
SNK 511-609	95	70	5	44	100	67	75.5	127.5	70	28	210	255	24	18	16	4.51
SNK 512-610	105	70	5	48	110	72	80.5	133	70	30	210	255	24	18	16	5.48
SNK 513-611	110	80	5	51	120	77	85.5	148.5	80	30	230	275	24	18	16	6.52
SNK 515-612	115	80	5	56	130	87	95.5	154.5	80	30	230	280	24	18	16	6.97
SNK 516-613	120	90	5	58	140	92.5	101	175.5	95	32	260	315	28	22	20	9.73
SNK 517	125	90	5	61	150	97.5	106	183	95	32	260	320	28	22	20	10.35
SNK 518-615	140	100	5	65	160	102.5	111	193	100	35	290	345	28	22	20	13.21
SNK 519-616	145	100	6	68	170	131	141	210	112	35	290	345	28	22	20	14.01
SNK 520-617	160	110	6	70	180	137.5	147.5	215	112	40	320	380	32	26	24	16.33
SNK 522-619	175	120	6	80	200	147.5	157.5	239	125	45	350	410	32	26	24	22.97
SNK 524-620	185	120	6	86	215	157.5	167.5	271	140	45	350	410	32	26	24	27.94
SNK 526	190	130	6	90	230	167.5	177.5	290	150	50	380	445	35	28	24	32.94
SNK 528	205	150	6	98	250	177.5	187.5	302	150	50	420	500	42	35	30	38.62
SNK 530	220	160	6	106	270	192.5	202.5	323	160	60	450	530	42	35	30	46.97
SNK 532	235	160	6	114	290	202.5	212.5	344	170	60	470	550	42	35	30	59.06

NOTES:

- SNK/SNU housings can be equipped with TSNG, U-LOK, TSNA, TS-U & TS-UF seals.
- Weight is only for reference.